



TYPICAL PROPERTIES

Total Base Number	10 mgKOH/g
Density, g/cm ³ @ 15°C	0.868
Flash Point	210°C
Pour Point	-45°C
Viscosity	
Kinematic Viscosity, 40°C	134 cSt
Kinematic Viscosity, 100°C	18 cSt
Viscosity Index	169

HyperDrive KXR

15W50 Fully Synthetic Racing Motor Oil

CODE: KXEEP52

100% Full Synthetic competition grade racing oil designed for petrol/diesel engines. Formulated using Group III and Group V synthetic base technology combined with the latest additive technology for maximum race performance. HyperDrive racing oils are recommended for fast road and racing use. This grade is applicable for the larger race or rally engines especially when under severe stress conditions. Particularly designed for normally aspirated and turbo-charged engines from 2 litres upwards.

FEATURES / BENEFITS

- Excellent protection against wear throughout the engine
- Excellent piston deposit control
- Good protection against sludge formation

PERFORMANCE / SPECIFICATIONS

- API: SN/CF
- ACEA: A3/B4

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
30-11-2020

HyperDrive Lubricants Limited Heming Road, Redditch, B98 0EA
Tel: 01527 502 252 Fax: 01527 502 253 hyperdrivelubricants.com