



## TYPICAL PROPERTIES

Density, g/cm <sup>3</sup> @ 15°C	0.880
Flash Point	208°C
Pour Point	-40°C
Viscosity	
Kinematic Viscosity, 40°C	64 cSt
Kinematic Viscosity, 100°C	10.8 cSt
Viscosity Index	137

## HyperDrive KXR

# 5W30 Fully Synthetic Engine Oil

**CODE:** KXEEC43

5W/30 Fully Synthetic Motor Oil is a super multi-grade engine oil produced from high quality synthetic base oils incorporating the latest additive technology to produce a super high performance engine oil that delivers excellent performance as well as good fuel economy.

## FEATURES / BENEFITS

- Excellent Fuel Efficiency and Sludge Control for Stop-Go City Motoring
- Excellent High and Low Temperature Performance
- Exceptional Long Term Anti-Wear Characteristics
- Very High Standard of Engine Cleanliness
- Long-lasting Dispersant Performance and Corrosion Protection
- Protects against Ring Sticking at High Temperatures
- Reduced Oil Consumption and Emissions

## PERFORMANCE / SPECIFICATIONS

- API: SN/CF
- ACEA: A1-12/B1-12
- ILSAC: GF-3
- BMW LL-01
- Ford: WSS-MC2 913A, WSS-MC2 913B

## AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:  
16-01-2022

HyperDrive Lubricants Limited Heming Road, Redditch, B98 0EA  
Tel: 01527 502 252 Fax: 01527 502 253 [hyperdrivelubricants.com](http://hyperdrivelubricants.com)