



TYPICAL PROPERTIES

| | |
|-----------------------------------|----------|
| Density, g/cm ³ @ 15°C | 0.880 |
| Flash Point | 208°C |
| Pour Point | -40°C |
| Viscosity | |
| Kinematic Viscosity, 40°C | 64 cSt |
| Kinematic Viscosity, 100°C | 10.8 cSt |
| Viscosity Index | 137 |

HyperDrive KXR

5W30 Fully Synthetic Engine Oil

CODE: KXEEC43

5W/30 Fully Synthetic Motor Oil is a super multi-grade engine oil produced from high quality synthetic base oils incorporating the latest additive technology to produce a super high performance engine oil that delivers excellent performance as well as good fuel economy.

FEATURES / BENEFITS

- Excellent Fuel Efficiency and Sludge Control for Stop-Go City Motoring
- Excellent High and Low Temperature Performance
- Exceptional Long Term Anti-Wear Characteristics
- Very High Standard of Engine Cleanliness
- Long-lasting Dispersant Performance and Corrosion Protection
- Protects against Ring Sticking at High Temperatures
- Reduced Oil Consumption and Emissions

PERFORMANCE / SPECIFICATIONS

- API: SN/CF
- ACEA: A1-12/B1-12
- ILSAC: GF-3
- BMW LL-01
- Ford: WSS-MC2 913A, WSS-MC2 913B

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
13-06-2021

HyperDrive Lubricants Limited Heming Road, Redditch, B98 0EA
Tel: 01527 502 252 Fax: 01527 502 253 hyperdrivelubricants.com