



TYPICAL PROPERTIES

Density, g/cm ³ @ 15°C	0.860
Flash Point, COC	220°C
Pour Point	-35°C
Viscosity	
Kinematic, @ 40°C	61 cSt
Kinematic, @ 100°C	11.7 cSt
Viscosity Index	191

HyperDrive KXR

5W30 GM Fully Synthetic

CODE: KXEEU40

Fully Synthetic 5W/30 GM is formulated according to the requirements of GM/Vauxhall/Opel petrol and diesel vehicles operating under extended drain intervals. Formulated from high quality synthetic base oils with additive technology especially designed to ensure high cleanliness and prolonged lubricant life it delivers excellent engine performance with reduced emissions and good fuel economy. Fully Synthetic 5W/30 GM provides optimum engine protection even when operating under extreme hot and cold climate conditions, yet maintains maximum performance throughout.

FEATURES / BENEFITS

- Suitable for GM/Vauxhall/Opel Petrol and Diesel vehicles operating under extended drain intervals
- Excellent High and Low Temperature Performance
- Excellent Fuel Efficiency and Sludge Control for Stop-Go City Motoring
- Very High Standard of Engine Cleanliness
- Long-Lasting Performance and Corrosion Protection
- Reduced Oil Consumption and Emissions

PERFORMANCE / SPECIFICATIONS

- API: SL/CF
- ACEA: A3/B3, A3/B4
- MB: 229.3
- GM: LL-025-A/B
- BMW: Longlife 01
- VW: 502.00, 505.00

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
22-07-2019

HyperDrive Lubricants Limited Heming Road, Redditch, B98 0EA
Tel: 01527 502 252 Fax: 01527 502 253 hyperdrivelubricants.com