



## TYPICAL PROPERTIES

Total Base Number	10 mgKOH/g
Density, g/cm <sup>3</sup> @ 15°C	0.860
Flash Point	210°C
Pour Point	-35°C
Viscosity	
Kinematic Viscosity, 40°C	55 cSt
Kinematic Viscosity, 100°C	9.5 cSt
Viscosity Index	157

## HyperDrive KXR

# 5W30 FORD 913D Full Synthetic Engine Oil

**CODE:** KXEEP40

HyperDrive 5W/30 FS 913D is a fully-synthetic high performance motor oil that delivers outstanding performance with high fuel economy and is suitable for use in Ford vehicles requiring Ford M2C 913D specified performance levels.

## FEATURES / BENEFITS

- Excellent protection against wear throughout the engine
- Excellent piston deposit control
- Good protection against sludge formation

## PERFORMANCE / SPECIFICATIONS

- API: SN/CF\*
- ACEA: A5-12/B5-12
- Ford: M2C 913D / 913C
- RN 0700
- STJLR 03.5003

## AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:  
6-12-2022

HyperDrive Lubricants Limited Heming Road, Redditch, B98 0EA  
Tel: 01527 502 252 Fax: 01527 502 253 [hyperdrivelubricants.com](http://hyperdrivelubricants.com)