



TYPICAL PROPERTIES

TBN, mgKOH.g-1	8
Density, g/cm ³ @ 15°C	0.850
Flash Point, COC	226°C
Pour Point	-40°C
Viscosity	
Kinematic, @ 40°C	95 cSt
Kinematic, @ 100°C	14.4 cSt
Viscosity Index	156

HyperDrive KXR

5W40 PD Full Synthetic (Mid SAPS)

CODE: KXEER41

5W/40 PD 505.01 FS Motor Oil is a fully synthetic engine oil produced from high quality synthetic base oils and high level performance additives, especially formulated for use in VW, Audi, Skoda and Ford vehicles fitted with VW unit injector diesel engines.

FEATURES / BENEFITS

- Suitable for use in petrol and diesel engines requiring VW specified 505.01 lubricant performance
- Blended to ensure fuel efficiency, reduced wear and low emissions.
- Mid-low SAPS technology delivers a high level of engine cleanliness and protection from combustion contamination.
- Provides optimum performance and engine protection at temperature extremes and under high performance conditions.
- Recommended for vehicles 2004-2008 requiring A3,B3,B4

PERFORMANCE / SPECIFICATIONS

- VW: 502/505.01
- ACEA:C3-12
- API: SN/CF
- BMW: LL-04
- MB: 226.5 229.31 229.51
- Porsche A40
- FORD: WSS-M2C917A
- GM Dexos 2
- Renault RN 0700, RN 0710

AVAILABILITY



① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
6-12-2022

HyperDrive Lubricants Limited Heming Road, Redditch, B98 0EA
Tel: 01527 502 252 Fax: 01527 502 253 hyperdrivelubricants.com