



TYPICAL PROPERTIES

TBN	10.3 mgKOH/g
Density, g.cm-3 @ 15°C	0.893
Flash Point, COC	220°C
Pour Point	-30°C
Sulphated Ash	1.17%
Viscosity	
Kinematic, 40°C	86 cSt
Kinematic, 100°C	11.2 cSt
Viscosity Index	128

AgriDrive KX+

Super Universal Tractor Oil SUTO 15W30 SL/CG-4

CODE: KAEEE10

Super Universal Tractor Oil (SUTO) is a high quality/high performance engine oil that meets all the lubrication requirements of farm tractors and agricultural machinery. SUTO is a multi-grade viscosity oil that spans a wide temperature range and is suitable for use in a variety of engines including naturally aspirated and turbocharged diesel and petrol engines. It is suitable for use in tractor hydraulic, transmission, and wet brake systems as well as gear boxes in all farm machinery. SUTO provides excellent protection under the most arduous operating conditions and is formulated according to the most demanding performance requirements. SUTO includes friction modifier additives to provide smooth operation of the wet brake system to prevent squawk and chatter. SUTO offers the convenience of a single lubricant approach that delivers top performance and avoids the need for stocking of multiple lubricants eliminating the risk of incorrect use in the field.


FEATURES / BENEFITS

- Excellent Thermal Stability
- Reduced Fuel Consumption
- Low Drag Formulation
- Reduced Friction
- Rapid Circulation on Start-up
- Excellent Anti-wear Protection
- Reduces Oil Inventory
- Lower Emissions
- Resists Black Sludge
- Improved Engine Cleanliness
- Low Oil Consumption
- Low Chlorine Formulation (for safe disposal or recycling)

PERFORMANCE / SPECIFICATIONS

- API SL/CG-4
- MIL-L-2104C/D, MIL-L-45199B
- Caterpillar Series 3
- Ford ESN-86A/B
- Ford M2C 159B
- Ford M2C 134D
- John Deere: JD 303, JD 20A, J20C, J14B
- Case: MS 1206
- Massey-Ferguson: 1139, M1135, M1127A
- MIL-L-2105
- API GL4
- IH B6

AVAILABILITY



ⓘ Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

Version Date:
3-06-2020

HyperDrive Lubricants Limited Heming Road, Redditch, B98 0EA
Tel: 01527 502 252 **Fax:** 01527 502 253 hyperdrivelubricants.com

To order call: 01527 502 252

keraxhyperdrive.com