



### AgriDrive KX+

## Milking Machine Oil

**CODE:** KAEQA10

Premium quality milking machine oil formulated from high viscosity index solvent refined mineral base oils with additives to provide excellent protection against oxidation, corrosion, wear and foaming.

### PERFORMANCE / SPECIFICATIONS

- DIN 51524, Part 2 (HLP) ISO 6743/4, Type: HM Vickers: I-286-S

### AVAILABILITY



### TYPICAL PROPERTIES

Type	HM
Kinematic Viscosity at 0°C, cSt	925
Kinematic Viscosity at 20°C, cSt	200
Kinematic Viscosity at 40°C, cSt	68
Kinematic Viscosity at 100°C, cSt	8.6
Viscosity Index	100
Flash Point, COC, °C	232
Pour Point °C	-28
Density, g.ml-1	0.88
ASTM D943: 1000 hr TOST TAN	<2.0 mgKOH.g-1
IP154: Copper Corrosion	Pass - Rating 1
DIN 51389: Vickers Vane Pump, Wt Loss	<50 mg
ASTM D1401: Demulse, Mins	21
IP 153B: Salt Water Corrosion	Pass
IP 313: ARV 50°C, 0.2% Air	9
IP 146: Foaming Tendency / Stability	
Sequence I	40/0
Sequence II	10/0
Sequence III	40/0
IP 278: Seal Compatibility	7.5

① Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

**Version Date:**  
15-08-2020

HyperDrive Lubricants Limited Heming Road, Redditch, B98 0EA  
**Tel:** 01527 502 252 **Fax:** 01527 502 253 [hyperdrivelubricants.com](http://hyperdrivelubricants.com)