

# HYPERDRIVE"



## **TYPICAL PROPERTIES**

Kinematic Viscosity, @ 100°C	11.8 cSt
Kinematic Viscosity, @ 40°C	133 cSt
Viscosity Index	101
Pour Point	-12°C
Flash Point, COC	221°C
Density, @ 15°C	0.888 g/cm³

HyperDrive KX+
SAE 30 SF/CF Engine Oil

CODE: KXEED29

HyperDrive KX+ SAE 30 SF/CF is a high quality engine oil, suitable for use in petrol and diesel engines requiring an SAE 30 monograde lubricant meeting the specifications below.

Blended with high performance additives and base oils, it protects against wear, rust and corrosion, maintaining engine condition and performance throughout the oil drain interval.

## **FEATURES / BENEFITS**

- · Anti-wear additives protect engines from wear, extending engine life
- Good oxidation stability maintains oil viscosity, ensuring suitable lubrication throughout the oil drain interval
- Detergent additives reduce the build-up of sludges, deposits and varnishes, maintaining engine condition
- Corrosion inhibitors protect against rust and corrosion, preserving engine performance

## PERFORMANCE SPECIFICATIONS

HyperDrive KX+ SAE 30 SF/CF is suitable for use where the following specifications are required:

• API: SF/CF

### **AVAILABILITY**











Hyperdrive, 47 Heming Road, Redditch, B98 0EA **Tel:** 0800 371 910 **hyperdrivelubricants.com**