





TYPICAL PROPERTIES

Appearance	Red Fluid
Kinematic Viscosity, @ 100°C	7.4 cSt
Kinematic Viscosity, @ 40°C	36.6 cSt
Viscosity Index	175cP
Pour Point	-48°C
Flash Point, COC	212°C
Density, @ 15°C	0.851 g/cm ³

HyperDrive KX ATF Dexron III

CODE: KXEMM10

HyperDrive KX ATF Dexron III is a high performance automatic transmission fluid. The low viscosity formulation, blended in high quality base oils with an optimised additive package, is designed to give excellent wear control across a wide range of temperatures, and long oil life. Will protect against wear, corrosion and oxidation maintaining performance and efficiency throughout the recommended oil drain interval.

FEATURES / BENEFITS

- Optimised additive package designed to meet Ford Mercon and General Motors Dexron IIIH performance requirements. Backwards compatible with older specifications
- Carefully balanced formulation provides excellent anti-wear performance and thermal stability, maintaining transmission system cleanliness and performance
- High quality, low viscosity base oils ensure good low temperature performance, protecting even from cold start, whilst also increasing oxidation and thermal stability, extending the oil drain interval
- Strong friction durability maintains optimal friction characteristics throughout the oil drain, leading to smooth gear shifting and maintaining efficiency of power transfer
- Designed to ensure longer oil life, improved foam control and better friction control compared to older specifications

PERFORMANCE SPECIFICATIONS

HyperDrive KX ATF Dexron III is suitable for use where the following specifications are required:

- ALLISON: C4
- CAT: TO-2
- FORD: Mercon
- GM: Dexron IIIH
- MB: 236.2

AVAILABILITY



Values are typical of current production, and whilst future production will meet these specifications, some variation in typical data may occur.

To order call: +44 800 371 910

hyperdrivelubricants.com